

# NI-9381

# Specifications

# Contents

NI-9381 Specifications..... 3

## NI-9381 Specifications

### Definitions

**Warranted** specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

**Characteristics** describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are **Typical** unless otherwise noted.

#### Related information:

- [Software Support for CompactRIO, CompactDAQ, Single-Board RIO, R Series, and EtherCAT](#)

### Conditions

Specifications are valid for the range -40 °C to 70 °C unless otherwise noted.

### Analog Input

Number of channels	8 single-ended channels
ADC resolution	12 bits
Type of ADC	Successive approximation register (SAR)

Input range	0 V to 5 V $\pm 1\%$
DNL	$\pm 1.25$ LSB
Conversion time	50 $\mu$ s (20 kS/s)
Input coupling	DC
Input impedance	1 M $\Omega$ in parallel with 50 pF
Bandwidth	1 kHz
<b>Stability</b>	
Gain drift	80 ppm/ $^{\circ}$ C
Offset drift	85 $\mu$ V/ $^{\circ}$ C

**Table 1.** Accuracy<sup>1</sup>

Measurement Conditions		Percent of Reading (Gain Error)	Percent of Range (Offset Error)
Calibrated	Maximum (-40 $^{\circ}$ C to 70 $^{\circ}$ C)	$\pm 0.70\%$	$\pm 13$ mV
	Typical (23 $^{\circ}$ C, $\pm 5$ $^{\circ}$ C)	$\pm 0.15\%$	$\pm 6.5$ mV
Uncalibrated <sup>2</sup>	Maximum (-40 $^{\circ}$ C to 70 $^{\circ}$ C)	$\pm 1.00\%$	$\pm 16$ mV
	Typical (23 $^{\circ}$ C, $\pm 5$ $^{\circ}$ C)	$\pm 0.50\%$	$\pm 7.5$ mV

<sup>1</sup> Accuracy is impacted for AC signals by an amount equal to  $4.0f$   $\mu$ V, where  $f$  is the signal frequency in hertz

<sup>2</sup> Uncalibrated accuracy refers to the accuracy achieved when acquiring in raw or unscaled modes where the calibration constants stored in the module are not applied to the data.

## Analog Output

Number of channels	8 channels
DAC resolution	12 bits
Type of DAC	String
Startup voltage	0 V
Output range	0 V to 5 V $\pm 1\%$
Current drive	$\pm 1$ mA
Output impedance	5 $\Omega$
Update time	50 $\mu$ s (20 kS/s)
Short-circuit protection	Indefinitely
Slew rate	30 V/ms
Settling time	900 $\mu$ s
DNL	$\pm 1$ LSB
Capacitive drive	1,500 pF
<b>Stability</b>	
Gain drift	85 ppm/ $^{\circ}$ C
Offset drift	180 $\mu$ V/ $^{\circ}$ C

Table 2. Accuracy<sup>3</sup>

Measurement Conditions		Percent of Reading (Gain Error)	Percent of Range (Offset Error)
Calibrated	Maximum (-40 °C to 70 °C)	±1.02%	±23.5 mV
	Typical (23 °C, ±5 °C)	±0.19%	±5 mV
Uncalibrated <sup>4</sup>	Maximum (-40 °C to 70 °C)	±1.9%	±50 mV
	Typical (23 °C, ±5 °C)	±0.6%	±10 mV

## Digital Input/Output

Number of channels	4 channels
Default power-on line direction	Input
Input/output type	LVTTL, single-ended
<b>Digital logic levels</b>	
Maximum input voltage	5.2 V
Input high, $V_{IH}$	2 V
Input low, $V_{IL}$	0.8 V
<b>Output high, <math>V_{OH}</math></b>	
Sourcing 100 $\mu$ A	2.7 V
<b>Output low, <math>V_{OL}</math></b>	

<sup>3</sup> Accuracy is impacted for AC signals by an amount equal to  $4.0f \mu\text{V}$ , where  $f$  is the signal frequency in hertz

<sup>4</sup> Uncalibrated accuracy refers to the accuracy achieved when acquiring in raw or unscaled modes where the calibration constants stored in the module are not applied to the data.

Sinking 100 $\mu$ A	0.2 V
Maximum I/O switching frequency	1 MHz
Capacitive drive	100 pF

## Safety Voltages

<b>Isolation</b>	
Channel-to-channel	None
Channel-to-earth ground	None

## Environmental Characteristics

<b>Temperature</b>	
Operating	-40 °C to 70 °C
Storage	-40 °C to 85 °C
<b>Humidity</b>	
Operating	10% RH to 90% RH, noncondensing
Storage	5% RH to 95% RH, noncondensing
Ingress protection	IP40
Pollution Degree	2
Maximum altitude	2,000 m
<b>Shock and Vibration</b>	

Operating vibration	
Random	5 g RMS, 10 Hz to 500 Hz
Sinusoidal	5 g, 10 Hz to 500 Hz
Operating shock	30 g, 11 ms half sine; 50 g, 3 ms half sine; 18 shocks at 6 orientations

To meet these shock and vibration specifications, you must panel mount the system.

## Power Requirements

Power consumption from chassis	
Active mode	600 mW maximum
Sleep mode	1 mW maximum
Thermal dissipation (at 70 °C)	
Active mode	600 mW maximum
Sleep mode	1 mW maximum

## Physical Characteristics

Dimensions	Visit <a href="https://ni.com/dimensions">ni.com/dimensions</a> and search by module number.
Weight	145 g (5.1 oz)