


Ventrix 560




Features

- Intel® 6th Generation Processor
- Intel® AMT 11 support
- PCIe revision 3.0 support
- Road map industrial components
- Mission critical 24/7 applications
- Custom colours and OEM branding (optional)
- Assembled and tested under ISO9001


Dimensions




Rear View



Top View



Front View



Side View

Ventrix 560

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

Specifications

Hardware specification	CPU: Intel® LGA 1151 6th Generation Core™ Processors Chipset: Q170 RAM: 2 x 288 pin DDR4 2133MHz un-buffered (up to 32GB*) Video: Intel® HD Graphics (530) Display Resolution: WDT: 225 levels; 1-255 sec. *Usable memory capacity may be limited by the Operating System	Environmental operational	Acoustic noise: 47dBA sound pressure at 23°C (typical) 49dBA* Temperature: 0 to 40°C (tested for operation up to 50°C) Humidity: 5 to 90% at 25°C non-condensing Low noise fan options are available (maximum operating temperature 35°C) We can design systems to meet additional requirements * Thermally controlled system fans run at peak operating speed during system start up. Speed is reduced based system temperature.
		Environmental storage	Temperature: -20 to 65°C
BIOS	AMI uEFI BIOS	Electromagnetic compatibility (EMC)	EN55022 Class A EN55024 Industrial severity (where applicable) Electrostatic discharge immunity test (EN61000-4-2) ±4kV Contact, applied to enclosure port ±8kV Air, applied to enclosure port ±4kV Indirect, applied to coupling plane Radiated, radio-frequency, electromagnetic field immunity test (EN61000-4-3) 80-1000MHz, 10 V/m (RMS, no modulation) 80% Modulation with 1kHz Sine wave Electrical fast transient/burst immunity test (EN61000-4-4) Power port AC, inc. protective earth Severity ±2kV Surge Immunity test (EN61000-4-5) Power port AC Severity ±2kV applied line to line Severity ±2kV applied line to earth Immunity to conducted disturbances induced by radio frequency fields (EN61000-4-6) Power port AC, inc. protective earth via CDN M3 0.15-80MHz, 10 V/m (no modulation) 80% Modulation with 1kHz Sine wave, applied via CDN type M3 Voltage dips, short interrupts and voltages variations immunity tests (EN61000-4-11) Power port AC >95% Reduction, 0.5 Periods >30% Reduction, 25 Periods >95% Reduction, 250 Periods Voltage dips, short interrupts and voltages variations immunity tests (EN61000-6-2) Power port AC >30% Reduction, 0.5 Periods >60% Reduction, 25 Periods >100% Reduction, 250 Periods Limits for harmonic current measurement (EN 61000-3-2), Product Class D Limitation of voltage changes, voltage fluctuations and flicker (EN 61000-3-3) Amplicon own a fully equipped EMC facility and can provide many additional tests to meet your requirements.
Storage	500GB SATA HDD DVDRW (standard height) Total drive capacity: 2 x 5.25", 2 x 3.5" HDD We can provide storage and backup solutions for any application		
System expansion	5 PCI (1 x full length, 4 x 180mm) 1 x PCI Express x16 (240mm length) for graphics card only Additional slots can be made available by reducing I/O ports		
Supported OS (Operating System)	Microsoft Windows 7/8. 1/10 (32/64-bit) Linux *Other operating available on request		
Internal interfaces	1 x PS/2 breakout (for keyboard and mouse) 1 x RS232/422/485 (Software selectable)* 5 x RS232* 6 x SATA III (RAID support 0/1/5/10) 1 x Audio HD 4 x USB 2.0 *Via DB9 breakout		
LEDs and switches	Power (PC ON) LED Hard disk access LED Front: ATX system control switch, system reset		
External interfaces	Front USB: 2 ports Front keyboard: Mini-DIN for (keyboard only) Rear USB: 2 x USB 3.0 ports on faceplate Serial: COM 1~4* (9 pin D-Type) VGA: DB-15 connector x 1 LAN: RJ45 Ethernet x 2 *Additional rear I/O can be broken out with breakout cables. Please discuss your requirements.		
Mechanical	Design: Desktop or wall mount Construction: Heavy duty cold rolled electroplated steel Colour: Black (custom colours available for large orders) Dimensions: 350(W) x 177(H) x 411(D) mm (13.8" x 7.0" x 16.2") Packaging size: 490(W) x 324(H) x 558(D) mm (19.3" x 12.8" x 22.0") Total drive capacity: 2 x 5.25", 1 x 3.5" HDD, 1 x 3.5" floppy disk drive Cooling: 1 x 120mm fan, 90 CFM Air filter: Removable (washable) Gross weight: Approximately 17kg	Safety	Safety of information technology equipment (EN 60950)
		Electrical ratings	Voltage: 90 ~ 264 VAC full range Frequency: 47 ~ 63Hz Input current: 8.0 / 4.0A for 115 / 230 VAC Inrush current: 65A / 125A max Typical operational current: 0.5 ~1A (base system) PSU maximum secondary loading: 460W Active PFC EMI noise filter Over power / voltage / current protection Short circuit protection
		Reliability	Reliability System MTBF: >25,000 hrs @ 25°C Diagnostic burn-in run on every system Typical Power 150W (unexpanded)

Sales: +44 (0) 1273 570 220 Admin: +44 (0) 1273 608 331 Fax: +44 (0) 1273 570 215 Website: www.amplicon.com Email: sales@amplicon.com